

Application No. 10/711,988
Docket No. A4-1854
Amendment dated April 25, 2006
Reply to Office Action of January 25, 2006

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

Claim 1 (Previously presented): A freestanding micrometer for determining the diameter of a cylindrical body, the freestanding micrometer comprising:

a housing;

means for supporting the housing on the cylindrical body while the cylindrical body is oriented so that its longitudinal axis is approximately horizontal, the support means enabling the freestanding micrometer to travel along a longitudinal length of the cylindrical body and comprising wheels that vertically support the housing on an upper surface of the cylindrical body, each of the wheels vertically supporting the housing on the upper surface having an axis of rotation oriented in a substantially vertical direction when supporting the housing on the upper surface of the cylindrical body;

first measurement means movably supported by the housing so that

Application No. 10/711,988
Docket No. A4-1854
Amendment dated April 25, 2006
Reply to Office Action of January 25, 2006

the position of the first measurement means can be altered in a lateral direction approximately perpendicular to the longitudinal axis of the cylindrical body, the first measurement means being adapted for sensing a first surface point of the cylindrical body laterally spaced apart from the housing and disposed in a cross-sectional plane of the cylindrical body, the first surface point defining a terminal of a chord lying in the cross-section plane of the cylindrical body;

second measurement means mounted to the housing for contact with a second surface point of the cylindrical body disposed in the cross-sectional plane of the cylindrical body, the second surface point defining a location along the length of the chord; and

means for determining the diameter of the cylindrical body based on the length and height of the chord ascertained from first and second outputs of the first and second measurement means, respectively.

Claim 2 (Original): The freestanding micrometer according to claim 1, wherein the housing is positioned on the cylindrical body while the cylindrical body is oriented so that the longitudinal axis of the cylindrical body is approximately horizontal, the second measurement means is positioned approximately top-dead-center on the cylindrical body and the chord is

Application No. 10/711,988
Docket No. A4-1854
Amendment dated April 25, 2006
Reply to Office Action of January 25, 2006

horizontal so that the second surface point locates the midpoint of the length of the chord, the length of the chord being ascertained by the position in the lateral direction of the first measurement means relative to the second measurement means.

Claim 3 (Original): The freestanding micrometer according to claim 1, wherein the determining means is programmed to calculate the diameter of the cylindrical body based on the formula

$$d = (c^2 + 4h^2)/4h$$

where d is the diameter of the cylindrical body, c is the length of the chord, and h is the height of the chord.

Claim 4 (Original): The freestanding micrometer according to claim 1, wherein the determining means comprises:

a computer outside the housing for calculating the diameter of the cylindrical body; and

means for transmitting the first and second outputs to the computer.

Claim 5 (Canceled)

Application No. 10/711,988
Docket No. A4-1854
Amendment dated April 25, 2006
Reply to Office Action of January 25, 2006

Claim 6 (Previously presented): The freestanding micrometer according to claim 1, wherein the wheels are supported by bearings having diameters larger than the diameters of the wheels.

Claim 7 (Original): The freestanding micrometer according to claim 6, further comprising means for sensing a distance the freestanding micrometer travels along the longitudinal length of the cylindrical body.

Claim 8 (Original): The freestanding micrometer according to claim 7, further comprising means for determining a profile of the cylindrical body along the longitudinal length thereof based on changes in the diameter of the cylindrical body determined at different locations along the longitudinal length of the cylindrical body.

Claim 9 (Currently amended): An electronic profile acquisition micrometer system for sensing the diameter and variations in the diameter of a cylindrical body while the cylindrical body is oriented so that its longitudinal axis is approximately horizontal, the micrometer system comprising:

a portable freestanding micrometer unit;

Application No. 10/711,988
Docket No. A4-1854
Amendment dated April 25, 2006
Reply to Office Action of January 25, 2006

means for supporting the micrometer unit on the cylindrical body while the cylindrical body is oriented so that its longitudinal axis is approximately horizontal, the supporting means comprising wheels disposed so as to contact an upper surface of the cylindrical body and thereby vertically support the micrometer unit on the upper surface, each of the wheels having an axis of rotation oriented in a substantially vertical direction when the micrometer unit is supported by the wheels on the upper surface of the cylindrical body, wherein the wheels are supported by bearings having diameters larger than the diameters of the wheels; and

means for determining the diameter of the cylindrical body as the micrometer unit travels on the upper surface along a longitudinal length of the cylindrical body while the wheels contact the upper surface of the cylindrical body and the axes of rotation of the wheels are substantially vertical.

Claim 10 (Previously presented): The electronic profile acquisition micrometer system according to claim 9, wherein the determining means is programmed to calculate the diameter of the cylindrical body based on the formula

$$d = (c^2 + 4h^2)/4h$$

Application No. 10/711,988
Docket No. A4-1854
Amendment dated April 25, 2006
Reply to Office Action of January 25, 2006

where d is the diameter of the cylindrical body, c is the length of a horizontal chord measured by the determining means, and h is the height of the horizontal chord.

Claim 11 (Canceled)

Claim 12 (Previously presented): The electronic profile acquisition micrometer system according to claim 9, further comprising means for sensing a distance the micrometer unit travels along the longitudinal length of the cylindrical body.

Claim 13 (Original): The electronic profile acquisition micrometer system according to claim 12, further comprising means for determining a profile of the cylindrical body along the longitudinal length thereof based on changes in the diameter of the cylindrical body continuously determined along the longitudinal length of the cylindrical body.

Claim 14 (Original): The electronic profile acquisition micrometer system according to claim 9, further comprising means for sensing a

Application No. 10/711,988
Docket No. A4-1854
Amendment dated April 25, 2006
Reply to Office Action of January 25, 2006

temperature of the cylindrical body adjacent at least one of the first and second surface points.

Claim 15 (Currently amended): A method of determining the diameter of a cylindrical body, the method comprising the steps of:

supporting a housing on the cylindrical body while the cylindrical body is oriented so that its longitudinal axis is approximately horizontal, the housing being vertically supported with wheels that contact an upper surface of the cylindrical body and have axes of rotation oriented in a substantially vertical direction while vertically supporting the housing on the upper surface of the cylindrical body; ~~and~~

determining the diameter of the cylindrical body while causing the housing to travel on the upper surface along a longitudinal length of the cylindrical body while the wheels contact the upper surface of the cylindrical body and the axes of rotation of the wheels remain substantially vertical;

positioning a first measurement means relative to the housing in a lateral direction approximately perpendicular to the longitudinal axis of the cylindrical body;

producing a first output signal with the first measurement means by

Application No. 10/711,988
Docket No. A4-1854
Amendment dated April 25, 2006
Reply to Office Action of January 25, 2006

sensing a first surface point of the cylindrical body laterally spaced apart from the housing and disposed in a cross-sectional plane of the cylindrical body, the first surface point defining a terminal of a chord lying in the cross-section plane of the cylindrical body; and

producing a second output signal with a second measurement means by sensing a second surface point of the cylindrical body adjacent the housing and disposed in the cross-sectional plane of the cylindrical body, the second surface point defining a location along the length of the chord;

wherein the diameter of the cylindrical body is determined based on the length and height of the chord ascertained from the first and second output signals.

Claims 16 and 17 (Canceled)

Claim 18 (Currently amended): The method according to claim 15, ~~claim 16,~~ wherein the first and second output signals are transmitted from the housing to a computer outside the housing, and the computer calculates the diameter of the cylindrical body.

Application No. 10/711,988
Docket No. A4-1854
Amendment dated April 25, 2006
Reply to Office Action of January 25, 2006

Claim 19 (Previously presented): The method according to claim 15,
further comprising the steps of:

sensing a distance the housing travels along the longitudinal length of
the cylindrical body; and

determining a profile of the cylindrical body along the longitudinal
length thereof based on changes in the diameter of the cylindrical body
determined at different locations along the longitudinal length.

Claim 20 (Original): The method according to claim 15, further
comprising the step of sensing a temperature of the cylindrical body.